

PILKEMASTER  
**SMART 1 & 2**

Easy and comfortable firewood chopping



# PILKEMASTER SMART 1 & 2

## Easy and comfortable firewood chopping



**Pilkemaster Smart** firewood processor is a new and comfortable way to chop firewood. It combines ease of use to modern safety features. Pilkemaster Smart firewood processor is attached to front linkage hydraulics of a machine such as tractor or wheel loader or to an excavator.

Due to new blade structure Pilkemaster Smart delivers clean cuts. Firewood is cut through to two pieces by a diagonal blade and centering press.

**Pilkemaster Smart 1 firewood processor** collects logs straight from a pile of wood or a wood trailer. Cutting and splitting can be done straight to a firewood sack, container or trailer. Compact size of Pilkemaster Smart makes working easy also with smaller machines. Smaller size makes also storage easier, it fits for example on top of a pallet.

**Pilkemaster Smart 2 firewood processor** is connected and functions like Smart 1 but feeding the unit is more efficient. Firewood can be fed to Pilkemaster Smart 2 for example by log loader with Pilkemaster pliers. Double feeding allows two logs to be fed at the same time doubling the results.

Technical specs, firewood processor	Smart 1	Smart 2
Weight	350 kg / 770 lb	465 kg / 1025 lb
Length	1945 mm / inch	2800 mm / 110,2 inch
Width	620 mm / 24,4 inch	620 mm / 24,4 inch
Height	1540 mm / 60 inch	1540 mm / 60 inch
Log length	250-410 mm / 9,8-16,1 inch	250-410 mm / 9,8-16,1 inch
Width of log, max.	190 mm / 7,48 inch	190 mm / 7,48 inch
Cutting and splitting speed max. (tuotto 40 l/min)	1,22 s	1,22 s
Pressing power	max. approx. 13 t	max. approx. 13 t
Recommended hydraulic output	approx. 40 l/min	approx. 40 l/min
Hydraulic pressure	180 - 250 bar	180 - 250 bar
Manufacturer	Agromaster Oy	Agromaster Oy
Dealer	<a href="http://www.pilkemaster.com">www.pilkemaster.com</a>	<a href="http://www.pilkemaster.com">www.pilkemaster.com</a>
<b>Note! All dimensions without reducers, extra feeding funnel or hose connectors</b>		
Accessories		
Extra feeding funnel	38 kg / 83,8 lb	2 x 38 kg / 2 x 83,8 lb
Coupler		
Hydraulic Connectors		